



Electrical & Automation

POWERING A NON-STOP INDIA



**Maximum Retail Prices
For Final Distribution Products**
Effective from 01-10-25

EXORA

FROM THE COO'S DESK.



Dear Partner,

As the festive season lights up homes and hearts across India, we extend our warmest wishes to you and your loved ones.

This time also marks an important milestone for us at **Lauritz Knudsen Electrical & Automation** - a moment to reflect, renew, and reaffirm our commitment to you.

Your continued trust and partnership have been the cornerstone of our journey. Building on a legacy of over 70 years, and following our refreshed identity last year, we remain focused on delivering **innovative, reliable, and high-quality products** that power progress.

As part of this journey, we are pleased to **share an updated price list**. This revision reflects our ongoing commitment to **transparency, quality, and excellence**, ensuring you continue to receive the best value and service.

This update also coincides with the launch of our **most extensive portfolio yet** - designed to support the evolving technology backbone of the nation.

At Lauritz Knudsen, our philosophy remains simple yet powerful: **We listen. We partner. We innovate.**

These words guide our actions and shape the way we grow - together.

We look forward to continuing our collaboration and powering up homes, industries, farms, infrastructure, businesses, and lives - with you by our side.

Wishing you a joyful festive season and continued success.

A handwritten signature in blue ink, reading "Naresh Kumar".

Warm regards,
Naresh Kumar
COO & Sr. VP, Electrical Standard Products
Lauritz Knudsen Electrical & Automation



Lauritz Knudsen Electrical & Automation Final Distribution Products

Lauritz Knudsen's Exora range of modular devices offer MCB, RCCB, Isolator & DB for final distribution of electrical power. Lauritz Knudsen's products are better known for reliability, functionality & ease of use.



Lauritz Knudsen products conform to relevant global standards viz. IEC, EN. They also have BIS, CE marking, CB and KEMA certification.

Contents

MCB - Miniature Circuit Breaker

2

Isolators, RCCBs

6

RCBOs - Residual Current Breaker with Overcurrent Protection

8

Other Protection & Control Devices

9

Industrial Plugs & Sockets

11

Distribution Boards

12



Note:

[Black colour : HSN code]


Current GST 18%, subject to changes as per Govt. notification





Safety re-defined

Finger proof terminals eliminate chances of accidental contact with live part. You can install, operate and maintain modular device with total confidence.



Energy limiting class - 3

If fault occurs, the Rapid Arc Quenching mechanism in modular device operates and extinguishes the arc quickly (within 3-5 msec), ensuring lowest possible energy flow through the circuit. This minimize risk of fire and maximizes life of your equipment.



Safety meets superior aesthetics

Ergonomically designed, profiled for superior cooling and manufactured with fire retardant material. Modular device is brought to you keeping in mind utmost user safety.

Key Benefits



True contact indication

E&A modular device range enhances safety through true contact indication even from a distance regardless of its mounting and knob position. Red and Green indication tags provided below the knob positively identify the electrical ON/OFF status, reflecting actual contact status.



Integrated label holder

E&A MCBs are equipped with label holder for easy identification of circuit during operation as well as in maintenance.



Innovatively profiled breathing channels

When two or more poles are placed adjacent to each other, the breathing channels are so profiled that the air circulates around individual pole, resulting in cooler operation.




Large terminal size and Biconnect

Exora MCB's can easily accommodate cables of up to 35 sq.mm. Biconnect terminals offer convenience of connecting both cable and bus bar.



Two position DIN rail clip

Installation on a DIN rail is further simplified with a two-position DIN rail clip as a standard feature. E&A MCB range makes mounting on a standard DIN rail more convenient.



Non-welding contacts

Silver Graphite contact tips ensure higher life and maximum safety against contact welding due to its superior anti-welding properties, enhancing safety and life of the system.



Combihead screw

E&A modular devices with combihead screws, allow you to use standard as well as Philips head screw drivers. E&A modular device range addresses your undefined needs.



Miniature Circuit Breaker (MCB) [8536]

Range Highlights

- › True contact indication for individual pole
- › Label holder facility for all configurations
- › Conforms to IS/IEC 60898 - 10kA
- › Conforms to IS/IEC 60947 - 2
 - » 15kA C-curve till 40 A
 - » 10kA C-curve for 50A, 63A
- › Available in B, C & D curves
- › Low watt loss - almost 50% of the values prescribed by IS/IEC 60898
- › Trip free mechanism
- › Design based on advanced current limiting hammer trip mechanism
- › No Line-Load bias
- › Bi connect feature on both sides
- › Suitable for accessory fitment



Rating	Modules 1 Mod = 17.5 mm	B-Curve Cat. No.	M.R.P. (₹) Per Unit	C-Curve Cat. No.	M.R.P. (₹) Per Unit	D-Curve Cat. No.	M.R.P. (₹) Per Unit
Single Pole (SP)							
0.5A	1	-	-	BB10E50C	500	BB10E50D	510
1A	1	-	-	BB10010C	500	BB10010D	510
2A	1	-	-	BB10020C	500	BB10020D	510
3A	1	-	-	BB10030C	500	BB10030D	510
4A	1	-	-	BB10040C	500	BB10040D	510
6A	1	BB10060B	294	BB10060C	294	BB10060D	425
10A	1	BB10100B	294	BB10100C	294	BB10100D	425
16A	1	BB10160B	294	BB10160C	294	BB10160D	425
20A	1	BB10200B	294	BB10200C	294	BB10200D	425
25A	1	BB10250B	294	BB10250C	294	BB10250D	425
32A	1	BB10320B	294	BB10320C	294	BB10320D	425
40A	1	BB10400B	700	BB10400C	700	BB10400D	765
50A	1	BB10500B	700	BB10500C	700	BB10500D*	765
63A	1	BB10630B	700	BB10630C	700	BB10630D*	765
Double Pole (DP)							
0.5A	2	-	-	BB20E50C	1410	BB20E50D	1430
1A	2	-	-	BB20010C	1410	BB20010D	1430
2A	2	-	-	BB20020C	1410	BB20020D	1430
3A	2	-	-	BB20030C	1410	BB20030D	1430
4A	2	-	-	BB20040C	1410	BB20040D	1430
6A	2	BB20060B	1000	BB20060C	1000	BB20060D	1040
10A	2	BB20100B	1000	BB20100C	1000	BB20100D	1040
16A	2	BB20160B	1000	BB20160C	1000	BB20160D	1040
20A	2	BB20200B	1000	BB20200C	1000	BB20200D	1040
25A	2	BB20250B	1000	BB20250C	1000	BB20250D	1040
32A	2	BB20320B	1000	BB20320C	1000	BB20320D	1040
40A	2	BB20400B	1630	BB20400C	1630	BB20400D	1700
50A	2	BB20500B	1630	BB20500C	1630	BB20500D*	1700
63A	2	BB20630B	1630	BB20630C	1630	BB20630D*	1700
Three Pole (TP)							
0.5A	3	-	-	BB30E50C	2050	BB30E50D	2080
1A	3	-	-	BB30010C	2050	BB30010D	2080
2A	3	-	-	BB30020C	2050	BB30020D	2080
3A	3	-	-	BB30030C	2050	BB30030D	2080
4A	3	-	-	BB30040C	2050	BB30040D	2080
6A	3	BB30060B	1575	BB30060C	1575	BB30060D	1660
10A	3	BB30100B	1575	BB30100C	1575	BB30100D	1660
16A	3	BB30160B	1575	BB30160C	1575	BB30160D	1660
20A	3	BB30200B	1575	BB30200C	1575	BB30200D	1660
25A	3	BB30250B	1575	BB30250C	1575	BB30250D	1660
32A	3	BB30320B	1575	BB30320C	1575	BB30320D	1660
40A	3	BB30400B	2455	BB30400C	2455	BB30400D	2570
50A	3	BB30500B	2455	BB30500C	2455	BB30500D*	2570
63A	3	BB30630B	2455	BB30630C	2455	BB30630D*	2570

Note: Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

*For details, please contact nearest branch office

Miniature Circuit Breaker (MCB) [8536]



Rating	Modules 1 Mod = 17.5 mm	B-Curve Cat. No.	M.R.P. (₹) Per Unit	C-Curve Cat. No.	M.R.P. (₹) Per Unit	D-Curve Cat. No.	M.R.P. (₹) Per Unit
Four Pole (FP)							
0.5A	4	-	-	BB40E50C	2580	BB40E50D	2585
1A	4	-	-	BB40010C	2580	BB40010D	2585
2A	4	-	-	BB40020C	2580	BB40020D	2585
3A	4	-	-	BB40030C	2580	BB40030D	2585
4A	4	-	-	BB40040C	2580	BB40040D	2585
6A	4	BB40060B	2180	BB40060C	2180	BB40060D	2235
10A	4	BB40100B	2180	BB40100C	2180	BB40100D	2235
16A	4	BB40160B	2180	BB40160C	2180	BB40160D	2235
20A	4	BB40200B	2180	BB40200C	2180	BB40200D	2235
25A	4	BB40250B	2180	BB40250C	2180	BB40250D	2235
32A	4	BB40320B	2180	BB40320C	2180	BB40320D	2235
40A	4	BB40400B	3060	BB40400C	3060	BB40400D	3310
50A	4	BB40500B	3060	BB40500C	3060	BB40500D*	3310
63A	4	BB40630B	3060	BB40630C	3060	BB40630D*	3310

Note: Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

*For details, please contact nearest branch office

MCBs (Miniature Circuit Breakers) : 80A-125A [8536]

Range Highlights

- Short circuit Breaking Capacity - 15kA (IS/IEC 60947-2, EN 60947-2)
- Suitable for Isolation
- C & D Characteristics
- Protection Degree - IP 20
- Available in SP, DP, TP and FP
- Availability of wide Range of Site Mountable Accessories



Rating	Modules 1 Mod = 17.5 mm	C Curve Cat. No.	M.R.P. (₹) Per Unit	D Curve Cat. No.	M.R.P. (₹) Per Unit
Single Pole (SP)					
80A	1.5	AU15S10803C	2940	AU15S10803D	3345
100A	1.5	AU15S11003C	3295	AU15S11003D	3745
125A	1.5	AU15S11253C	3545	AU15S11253D	4045
Double Pole (DP)					
80A	3	AU15S20803C	6515	AU15S20803D	7415
100A	3	AU15S21003C	6950	AU15S21003D	7905
125A	3	AU15S21253C	7650	AU15S21253D	8695
Three Pole (TP)					
80A	4.5	AU15S30803C	10280	AU15S30803D	11705
100A	4.5	AU15S31003C	10965	AU15S31003D	12460
125A	4.5	AU15S31253C	12165	AU15S31253D	13825
Four Pole (FP)					
80A	6	AU15S40803C	13425	AU15S40803D	15245
100A	6	AU15S41003C	13965	AU15S41003D	15890
125A	6	AU15S41253C	15815	AU15S41253D	17975

**CERTIFIED TO LEAD,
TRUSTED FOR SAFETY.**

BIS-Certified HR MCBs Range - 80A, 100A & 125A



(AC MCB + DC MCB)



AC MCB^A with C-Curve

Description	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
1 AC 16A DP MCB ^A + 1 DC 16A DP 500V MCB	2+2	SC221616	1805
New 1 AC 20A DP MCB ^A + 1 DC 25A DP 500V MCB	2+2	SC222020	1805
New 1 AC 20A DP MCB ^A + 1 DC 20A DP 500V MCB	2+2	SC222025	1805
New 1 AC 20A DP MCB ^A + 1 DC 32A DP 500V MCB	2+2	SC222032	1805
1 AC 25A DP MCB ^A + 1 DC 16A DP 500V MCB	2+2	SC222516	1805
New 1 AC 25A DP MCB ^A + 1 DC 25A DP 500V MCB	2+2	SC222525	1805
1 AC 32A DP MCB ^A + 1 DC 16A DP 500V MCB	2+2	SC223216	1805
New 1 AC 32A DP MCB ^A + 1 DC 25A DP 500V MCB	2+2	SC223225	1805
1 AC 32A DP MCB ^A + 1 DC 32A DP 500V MCB	2+2	SC223232	1805

Double the Protection, Twice the Power!

Complete Protection for
Solar Rooftop Installations

DC MCB:
10kA as per IEC 60947-2
AC MCB:
10kA as per IS/IEC 60898-1



Miniature Circuit Breaker (MCB) [8536]

DC MCBs as per IEC 60947-2 [8536]

Rated Voltage:

Breaking capacity of 6 kA - BB Series DC MCBs

130V DC SP MCB



Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
Single Pole (SP)			
0.5A	1	BB10E5DC	700
1A	1	BB1001DC	700
2A	1	BB1002DC	700
3A	1	BB1003DC	700
4A	1	BB1004DC	700
6A	1	BB1006DC	605
10A	1	BB1010DC	605
16A	1	BB1016DC	605
20A	1	BB1020DC	605
25A	1	BB1025DC	605
32A	1	BB1032DC	605
40A	1	BB1040DC	795
50A	1	BB1050DC	795
63A	1	BB1063DC	795

Rated Voltage:

Breaking capacity of BJ Series DC MCBs

» 10kA till 40 A

» 6kA for 50A, 63A

250V DC SP MCB

Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
Single Pole (SP)			
0.5A	1	BJ10E5DC	850
1A	1	BJ1001DC	850
2A	1	BJ1002DC	850
3A	1	BJ1003DC	850
4A	1	BJ1004DC	850
6A	1	BJ1006DC	695
10A	1	BJ1010DC	695
16A	1	BJ1016DC	695
20A	1	BJ1020DC	695
25A	1	BJ1025DC	695
32A	1	BJ1032DC	695
40A	1	BJ1040DC	960
50A	1	BJ1050DC	960
63A	1	BJ1063DC	960

New

250V DC DP MCB



Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
0.5A	2	BB20E5DC	1495
1A	2	BB2001DC	1495
2A	2	BB2002DC	1495
3A	2	BB2003DC	1495
4A	2	BB2004DC	1495
6A	2	BB2006DC	1315
10A	2	BB2010DC	1315
16A	2	BB2016DC	1315
20A	2	BB2020DC	1315
25A	2	BB2025DC	1315
32A	2	BB2032DC	1315
40A	2	BB2040DC	1780
50A	2	BB2050DC	1780
63A	2	BB2063DC	1780

500V DC DP MCB

Rating	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
0.5A	2	BJ20E5DC	1775
1A	2	BJ2001DC	1775
2A	2	BJ2002DC	1775
3A	2	BJ2003DC	1775
4A	2	BJ2004DC	1775
6A	2	BJ2006DC	1500
10A	2	BJ2010DC	1500
16A	2	BJ2016DC	1500
20A	2	BJ2020DC	1500
25A	2	BJ2025DC	1500
32A	2	BJ2032DC	1500
40A	2	BJ2040DC	1910
50A	2	BJ2050DC	1910
63A	2	BJ2063DC	1910

New

Note: Standard Pack Quantity for MCB : SP - 12 Nos., DP - 6 Nos.

1000V DC MCBs [8536]

Rated Voltage: 1000V DC

with breaking capacity of 6 kA - BK Series DC MCBs

New



Description	Modules 1 Mod = 17.5mm	Cat. No.	M.R.P. (₹) Per Unit
DP 6A 1000V DC 6kA MCB	4	BK2006DC	2355
DP 10A 1000V DC 6kA MCB	4	BK2010DC	2355
DP 16A 1000V DC 6kA MCB	4	BK2016DC	2355
DP 20A 1000V DC 6kA MCB	4	BK2020DC	2355
DP 25A 1000V DC 6kA MCB	4	BK2025DC	2355
DP 32A 1000V DC 6kA MCB	4	BK2032DC	2355
DP 40A 1000V DC 6kA MCB	4	BK2040DC	2860
DP 50A 1000V DC 6kA MCB	4	BK2050DC	2860
DP 63A 1000V DC 6kA MCB	4	BK2063DC	2860

Isolators [8536]



Range Highlights

- › Conforms to IEC 60947-3
- › Utilization category AC-22A
- › Available in DP, TP and FP versions in 40A, 63A, 80A & 100A ratings

Rating	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Double Pole (DP)				Three Pole (TP)		Four Pole (FP)			
40A	2	BF204000	625	3	BF304000	1090	4	BF404000	1410
63A	2	BF206300	805	3	BF306300	1270	4	BF406300	1475
80A	2	BF208000	1030	3	BF308000	1395	4	BF408000	1655
100A	2	BF210000	1070	3	BF310000	1485	4	BF410000	1785

Note: Standard Pack Quantity for Isolator : DP - 6 Nos., TP - 4 Nos., FP - 3 Nos.

RCCB (Residual Current Circuit Breaker) [8536]



Range Highlights

- › Conforms to IS 12640 (Part 1) / IEC 61008-1
- › RCCBs are available in DP and FP versions from 25 to 100A ratings with 30 mA, 100 mA and 300mA sensitivity



- › Truly current operated - operation even at nominal Voltage
- › Operates on Core Balance Current Transformer (CBCT) principle
- › Advanced neutral mechanism

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Double Pole (DP)				
25A	30 mA	2	BG202503	3380
	100 mA	2	BG202510	3585
	300 mA	2	BG202530	3585
40A	30 mA	2	BG204003	3795
	100 mA	2	BG204010	4100
	300 mA	2	BG204030	4100
63A	30 mA	2	BG206303	4735
	100 mA	2	BG206310	4945
	300 mA	2	BG206330	4945
100A	30 mA	2	BG210003	8425
	100 mA	2	BG210010	8530
	300 mA	2	BG210030	8530

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Four Pole (FP)				
25A	30 mA	4	BG402503	4425
	100 mA	4	BG402510	4635
	300 mA	4	BG402530	4635
40A	30 mA	4	BG404003	4470
	100 mA	4	BG404010	4710
	300 mA	4	BG404030	4710
63A	30 mA	4	BG406303	5055
	100 mA	4	BG406310	5405
	300 mA	4	BG406330	5405
100A	30 mA	4	BG410003	8725
	100 mA	4	BG410010	9050
	300 mA	4	BG410030	9050

RCCBs (Residual Current Circuit Breakers) : Type-Adi (with Added immunity) [8536]



Range Highlights

- › Wide Range of Current Ratings - 25A to 100A
- › Precise Sensitivities for variety of applications - from 30mA to 300mA
- › 2P & 4P versions
- › Suitable for Isolation
- › Protection Degree - IP 20
- › Availability of wide Range of Site Mountable Accessories
- › Type Adi: Suitable for AC + Pulsating DC (Type A) + Harmonics

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
2P Adi				
25A	30mA	2	AURAD202503	5815
	100mA	2	AURAD202510	6080
	300mA	2	AURAD202530	6080
40A	30mA	2	AURAD204003	6170
	100mA	2	AURAD204010	6270
	300mA	2	AURAD204030	6270
63A	30mA	2	AURAD206303	7220
	100mA	2	AURAD206310	7355
	300mA	2	AURAD206330	7355
100A	30mA	2	AURAD210003	10665

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
4P Adi				
25A	30mA	4	AURAD402503	7030
	100mA	4	AURAD402510	7165
	300mA	4	AURAD402530	7165
40A	30mA	4	AURAD404003	7300
	100mA	4	AURAD404010	7415
	300mA	4	AURAD404030	7415
63A	30mA	4	AURAD406303	7950
	100mA	4	AURAD406310	8115
	300mA	4	AURAD406330	8115
100A	30mA	4	AURAD410003	12665
	300mA	4	AURAD410030	12665

All-Rounder RCDs (RCCB & RCBO)

Specially designed Adi RCDs ensure Safe and Reliable protection
for All Applications in AC networks with Pulsating DC along with Harmonics



Added Immunity

RCBOs (Residual Current Breaker with Overcurrent Protection) [8536]

Range Highlights*

- › Conforms to IEC 61009-1, IS 12640-2, EN 61009-1
- › Short circuit Breaking Capacity - 10kA
- › Precise Sensitivities for a variety of applications
 - » from 10mA to 300mA
- › Suitable for Isolation

Type-AC

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
2P AC*				
6A	10mA	2	AUF3C200601	5405
	30mA	2	AUF3C200603	5405
	100mA	2	AUF3C200610	5515
	300mA	2	AUF3C200630	5580
10A	10mA	2	AUF3C201001	5405
	30mA	2	AUF3C201003	5405
	100mA	2	AUF3C201010	5515
	300mA	2	AUF3C201030	5580
16A	10mA	2	AUF3C201601	5405
	30mA	2	AUF3C201603	5405
	100mA	2	AUF3C201610	5515
	300mA	2	AUF3C201630	5580
20A	30mA	2	AUF3C202003	5405
	100mA	2	AUF3C202010	5515
	300mA	2	AUF3C202030	5580
25A	30mA	2	AUF3C202503	5405
	100mA	2	AUF3C202510	5515
	300mA	2	AUF3C202530	5580
32A	30mA	2	AUF3C203203	5405
	100mA	2	AUF3C203210	5515
	300mA	2	AUF3C203230	5580
40A	30mA	2	AUF3C204003	5405
	100mA	2	AUF3C204010	5515
	300mA	2	AUF3C204030	5580
63A	30mA	4	AUF3C206303	6415
	100mA	4	AUF3C206310	6805
	300mA	4	AUF3C206330	6860
4P AC				
16A	30mA	7.5	AUF3C401603	5800
	100mA	7.5	AUF3C401610	6460
	300mA	7.5	AUF3C401630	6590
20A	30mA	7.5	AUF3C402003	5800
	100mA	7.5	AUF3C402010	6460
	300mA	7.5	AUF3C402030	6590
25A	30mA	7.5	AUF3C402503	5800
	100mA	7.5	AUF3C402510	6460
	300mA	7.5	AUF3C402530	6590
32A	30mA	7.5	AUF3C403203	5990
	100mA	7.5	AUF3C403210	6465
	300mA	7.5	AUF3C403230	6605
40A	30mA	7.5	AUF3C404003	6085
	100mA	7.5	AUF3C404010	6465
	300mA	7.5	AUF3C404030	6625
63A	30mA	7.5	AUF3C406303	7290
	100mA	7.5	AUF3C406310	7425
	300mA	7.5	AUF3C406330	7425
80A	30mA	12	AUF3C408003	27740
	100mA	12	AUF3C408010	28360
	300mA	12	AUF3C408030	28360
100A	30mA	12	AUF3C410003	29655
	100mA	12	AUF3C410010	30365
	300mA	12	AUF3C410030	30365

*For 2P AC D Curve RCBO, please contact nearest branch office



- › Availability of wide Range of Site Mountable Accessories
- › Available in
 - » Type AC: For standard AC installations
 - » Type Adi: Suitable for AC + Pulsating DC (Type A) + Harmonics

Type-Adi

Rating	Sensitivity	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
2P Adi				
6A	30mA	2	AUF3D200603	7160
	100mA	2	AUF3D200610	7885
	300mA	2	AUF3D200630	8180
10A	30mA	2	AUF3D201003	7160
	100mA	2	AUF3D201010	7885
	300mA	2	AUF3D201030	8180
16A	30mA	2	AUF3D201603	7160
	100mA	2	AUF3D201610	7885
	300mA	2	AUF3D201630	8180
20A	30mA	2	AUF3D202003	7160
	100mA	2	AUF3D202010	7885
	300mA	2	AUF3D202030	8180
25A	30mA	2	AUF3D202503	7160
	100mA	2	AUF3D202510	7885
	300mA	2	AUF3D202530	8180
32A	30mA	2	AUF3D203203	7160
	100mA	2	AUF3D203210	7885
	300mA	2	AUF3D203230	8180
40A	30mA	2	AUF3D204003	7160
	100mA	2	AUF3D204010	7885
	300mA	2	AUF3D204030	8180
63A	30mA	4	AUF3D206303	8280
	100mA	4	AUF3D206310	8760
	300mA	4	AUF3D206330	8835
4P Adi				
16A	30mA	7.5	AUF3D401603	7480
	100mA	7.5	AUF3D401610	8320
	300mA	7.5	AUF3D401630	8490
20A	30mA	7.5	AUF3D402003	7480
	100mA	7.5	AUF3D402010	8320
	300mA	7.5	AUF3D402030	8490
25A	30mA	7.5	AUF3D402503	7480
	100mA	7.5	AUF3D402510	8320
	300mA	7.5	AUF3D402530	8490
32A	30mA	7.5	AUF3D403203	7720
	100mA	7.5	AUF3D403210	8325
	300mA	7.5	AUF3D403230	8500
40A	30mA	7.5	AUF3D404003	7835
	100mA	7.5	AUF3D404010	8325
	300mA	7.5	AUF3D404030	8535
63A	30mA	7.5	AUF3D406303	9390
	100mA	7.5	AUF3D406310	9580
	300mA	7.5	AUF3D406330	9580
80A	30mA	12	AUF3D408003	27740
	100mA	12	AUF3D408010	28360
	300mA	12	AUF3D408030	28360
100A	30mA	12	AUF3D410003	29655
	100mA	12	AUF3D410010	30365
	300mA	12	AUF3D410030	30365

*For technical details, please contact nearest branch office

SPDs (Surge Protection Devices) [8536]



New

Range Highlights

- › Conforms to IEC 61643-11
- › Available in Type 2 and Type 1+2
- › Type 2 : Protection against indirect lightning and switching surges
 - » Maximum Discharge Current - I_{max} up to 70kA
- › Type 1+2 : Protection against direct and indirect lightning surges
 - » Maximum Discharge Current - I_{max} up to 100kA

800V Solar Application

Description	Configuration	Modules 1 Mod = 17.5 mm	Voltage (Uc)	Cat. No.	M.R.P. (₹) Per Unit
Type 2, I _{max} 40kA	3P	4	1500	AUSP023P40-1500	12500
Type 1+2, I _{imp} 12.5kA	3P	5	1360	AUSP123P50-1360	41430
Type 1+2, I _{imp} 12.5kA	3P	4	880	AUSP123P50-880	30000

440V Application (Common + Differential Mode)

Description	I _{max}	Configuration	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Type 1+2, I _{imp} 12.5kA	50kA	1P+N	2	AUSP121PN50D	11070
		3P+N	4	AUSP123PN50D	21205
Type 2	40kA	1P+N	1	AUSP021PN40D	6920
		3P+N	2	AUSP023PN40D	13830
Type 2	15kA	1P+N	1	AUSP021PN15D	5535
		3P+N	2	AUSP023PN15D	10890
Type 1+2, I _{imp} 8kA	100kA	1P+N	2	AUSP121PN100D	9955
		3P+N	4	AUSP123PN100D	19555
Type 2	70kA	1P+N	2	AUSP021PN70D	10870
		3P+N	4	AUSP023PN70D	18100

SPD Cartridges

Description	Cat. No.	M.R.P. (₹) Per Unit
Cartridge for AUSP021PN15D	AUSC021PN15D	2720
Cartridge for AUSP021PN40D	AUSC021PN40D	3390
Cartridge for AUSP021PN70D / AUSP023PN70D	AUSC021PN70D	3625
Cartridge for AUSP023PN15D [#]	AUSC023PN15D	3560
Cartridge for AUSP023PN40D [#]	AUSC023PN40D	4525
Cartridge for AUSP121PN100D / AUSP123PN100D	AUSC121PN100D	5430
Cartridge for AUSP121PN50D / AUSP123PN50D	AUSC121PN50D	5860
Cartridge for AUSP023PN15D [#]	AUSC023PN15DG	4125
Cartridge for AUSP023PN40D [#]	AUSC023PN40DG	4305

[#]For technical details, please contact nearest branch office

ACCL (Automatic Changeover with Current Limiter) [8536]

Single Phase ACCL



Range Highlights

- › Conforms to IEC 60947-6, IEC 60947-3
- › Wide Range of Current Ratings
 - » (Generator side) - 1A to 30A
 - » (Electricity Board side) - 30A
- › RoHS compliant

Description EB/DG	Modules 1 Mod = 17.5 mm	CAT Nos.	M.R.P. (₹) Per Unit
30A/1A	4	AUCL01030001	2505
30A/1.5A	4	AUCL010301E5	2505
30A/2A	4	AUCL01030002	2505
30A/2.5A	4	AUCL010302E5	2505
30A/3A	4	AUCL01030003	2505
30A/4A	4	AUCL01030004	2505
30A/5A	4	AUCL01030005	2505
30A/6A	4	AUCL01030006	2505
30A/8A	4	AUCL01030008	2505
30A/10A	4	AUCL01030010	2505
30A/12A	4	AUCL01030012	2505
30A/15A	4	AUCL01030015	2505
30A/20A	4	AUCL01030020	2505
30A/30A	4	AUCL01030030*	2505

*Non-current limiting variant

Three Phase ACCL



Range Highlights

- › Settable overload current limit at DG side
- › Separate power consumption monitoring for Mains & Genset
- › Settable overvoltage & undervoltage protection
- › Settable TPN or SPN mode at DG side
- › Protection against single phasing

Description (AC-1) EB/DG	Cat. No.	M.R.P. (₹) Per Unit
32A / 32A	AUCL03032032	12295
40A / 32A	AUCL03040032	12670
40A / 40A	AUCL03040040	13715
50A / 50A	AUCL03050050	19545
63A / 50A	AUCL03063050	21570
63A / 63A	AUCL03063063	24430
80A / 80A	AUCL03080080	37235
125A / 125A	AUCL03125125	62680

For 3 Phase ACCL programming video
please scan the QR code or click here



Changeover Switches [8536]



Range Highlights

- › Conforms to IEC 60947-3 and IS/IEC 60947-3
- › Available in 3 positions (I-O-II) with centre off position
- › Utilization category AC-22A

Rating	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Double Pole			
25A	2	AUC00202500	1795
40A	2	AUC00204000	2745
63A	3	AUC00206300	3195
Four Pole			
40A	4	AUC00404000	4730
63A	6	AUC00406300	5365

Accessories

Accessories [8538]



All Half Module and One Module Accessories are common for 80A-125A MCBs, RCBOs and Adi RCCBs

Description	Configuration	Modules 1 Mod = 17.5 mm	Voltage	CAT Nos.	M.R.P. (₹) Per Unit
Auxiliary Contact	1NO+1NC	0.5	240V AC, 24V DC	AUAXAC240	1055
AUX/TAC*	1NO+1NC	0.5	240V AC, 24V DC	AUATAC240	1240
HR AUX/TAC*	1NO+1NC	0.5	240V AC, 24V DC	AUATAC240HR	1240
Undervoltage Release	-	1	240V AC	AUUVAC240	2500
Release	-	1	24V DC	AUUVDC024	2500
Overvoltage Release	-	1	240V AC	AUOVAC240	3090
Shunt Release	-	1	240V AC	AUSRAC240	2865
	-	1	24V DC	AUSRDC024	2865
Padlock-Suitable for Lock Hasp 3.5 - 5 mm dia. max	Suitable for 1Pole=1Mod devices: RCCBs, RCBOs, Changeover Switches up to 40A			AUPD01	565
	Suitable for 1Pole-1.5Mod devices: MCBs 80A-125A, Changeover Switch 63A			AUPD02	640

Note: Standard Pack Quantity for Padlock - 2 Nos.

*For 80A-125A MCBs please contact nearest branch office

Control & Monitoring Devices

Modular Contactors [8536]



Range Highlights

- › Wide Range of Current Ratings:
 - » 25A, 40A and 63A
- › Conforms to :
 - » IEC 61095, EN 61095
 - » IEC 60947-4-1, EN 60947-4-1
 - » IEC 60947-5-1
- › Protection Degree IP 20

Description (AC-1)	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
25A-1NO	1	AUMC1002501	2015
25A-2NO	1	AUMC2002501	2525
40A-2NO	3	AUMC2004003	4320
40A-3NO	3	AUMC3004003	6190
40A-4NO	3	AUMC4004003	7260
63A-2NO+2NC	3	AUMC2206303	7675
63A-3NO	3	AUMC3006303	7865
63A-4NO	3	AUMC4006303	8660
Accessory [8538]			
Auxiliary Contact, 2NO	0.5	AUMCAUX240	1880

Energy Meters [9030]



Range Highlights

- › DIN mounting whole current operated meter
- › Accuracy Class 1.0
- › Inbuilt RS485 option
- › **Parameters** : Voltage, Current, kW, kWh, kVA, kVAh, RPM, Load hours, Interruptions


Description	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
Single Phase - 60A	2	WD4010100000	3100
Three Phase - 80A	5	WD4020100000	6715
Single Phase - 60A (RS485)	2	WD4010110000	4585
Three Phase - 80A (RS485)	5	WD4020110000	10130

Indicating Lights [8531]



Description	Modules 1 Mod = 17.5 mm	Cat. No.	M.R.P. (₹) Per Unit
RED	1	AUIL01RED00	1160
YELLOW	1	AUIL01YEL00	1160
BLUE	1	AUIL01BLU00	1160
GREEN	1	AUIL01GRE00	1160
RED-YELLOW-BLUE	1	AUIL01RYB00	1410

Auxiliary & Accessories for Exora MCBs [8538]



Description	Cat. No.	M.R.P. (₹) Per Unit
Auxiliary Contact - 6A, 240V AC, (1NO+1NC), 0.5 Mod	BZA11006	985
Shunt Release - 240V AC, 1 Mod	BZS00240	2700
Trip Alarm Contact - 6A, 240V AC, (1NO+1NC), 0.5 Mod	BZT11006	1155

Plugs



Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
Plug - IP44		
16A, 2P+E	PSKPM30164	610
32A, 2P+E	PSKPM30324	960
16A, 3P+E	PSKPM40164	780
32A, 3P+E	PSKPM40324	1135
16A, 3P+N+E	PSKPM50164	820
32A, 3P+N+E	PSKPM50324	1095
Plug - IP67		
16A, 2P + E	PSKPM30167	1355
32A, 2P + E	PSKPM30327	1915
63A, 2P + E	PSKPM30637	5435
16A, 3P + E	PSKPM40167	1530
32A, 3P + E	PSKPM40327	2420
63A, 3P + E	PSKPM40637	5175
16A, 3P + N + F	PSKPM50167	1640
32A, 3P + N + E	PSKPM50327	2085
63A, 3P + N + E	PSKPM50637	5185
125A, 3P + N + E	PSKPM51257	15840

Socket



Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
Socket - IP44		
16A, 2P+E	PSKSM30164	845
32A, 2P+E	PSKSM30324	1180
16A, 3P+E	PSKSM40164	990
16A, 3P + N + E	PSKSM50164	1080
32A, 3P + N + E	PSKSM50324	1445
Socket - IP67		
16A, 2P+E	PSKSM30167	1590
32A, 2P+E	PSKSM30327	2185
63A, 2P+E	PSKSM30637	5915
16A, 3P+E	PSKSM40167	1995
63A, 3P+E	PSKSM40637	5970
16A, 3P + N + E	PSKSM50167	2085
32A, 3P + N + E	PSKSM50327	2440
63A, 3P + N + E	PSKSM50637	6065
125A, 3P + N + E	PSKSM51257	19040

Socket Angled



Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
Socket Angled - IP44		
16A, 2P+E	PSKSA30164	655
32A, 2P+E	PSKSA30324	1160
16A, 3P+E	PSKSA40164	990
32A, 3P+E	PSKSA40324	1370
16A, 3P+N+E	PSKSA50164	1055
32A, 3P+N+E	PSKSA50324	1340
Socket Angled - IP67		
16A, 2P+E	PSKSA30167	1250
32A, 2P+E	PSKSA30327	1630
63A, 2P+E	PSKSA30637	5340
32A, 3P+E	PSKSA40327	2420
63A, 3P+E	PSKSA40637	5350
32A, 3P+N+E	PSKSA50327	1930
63A, 3P+N+E	PSKSA50637	5455
125A, 3P+N+E	PSKSA51257	18105

Socket Straight



Highlights

- › Conforms to IEC 60309 -1&2
- › Mechanical Impact - IK08
- › Ingress Protection - IP44 & IP67
- › Fire Resistance - 850°C as per IEC 60695-2-11
- › Easy Screw connection with same orientation of clamp screws

Description	Cat NO	M.R.P. (₹) Per Unit
Socket Straight- IP44		
16A, 2P+E	PSKSS30164	750
32A, 2P+E	PSKSS30324	1190
32A, 3P+N+E	PSKSS50324	1490
Socket Straight- IP67		
16A, 2P+E	PSKSS30167	1260
63A, 2P+E	PSKSS30637	6465
63A, 3P+E	PSKSS40637	5400
63A, 3P+N+E	PSKSS50637	5400
125A, 3P+N+E	PSKSS51257	18105

Distribution Board suitable for Aluminum shuttering (Mivan) Construction



DBs suitable for Aluminum Shuttering Construction [8537]

SPN DBs

Highlights

- Available in CRCA sheet steel, RAL9003, powder coated
- Ready to use DBs - Provided with 100A insulated phase bus-bar | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification label
- With provision for DP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
IP 43 - Metal Door				
4 way	2	2	LTSD04M	*
6 way	2	4	LTSD06M	*
8 way	2	6	LTSD08M	*
12 way	2	10	LTSD12M	*
16 way	2	14	LTSD16M	*

TPN DBs

Highlights

- Available in CRCA sheet steel, RAL 9003, powder coated
- Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
IP 43 - Metal Door				
4 way	8	4+4+4	LTTD04M	*
6 way	8	6+6+6	LTTD06M	*
8 way	8	8+8+8	LTTD08M	*

* For details, please contact nearest branch office

DESIGN OR SAFETY?

OBVIOUSLY BOTH. OBVIOUSLY EXORA DBs.

Built to impress, engineered to protect - The new Exora Distribution Board sets the standard for style and safety.



Elegant,
Curved Door
Design



Safe push-type
latch for
enhanced safety



Superior Gasketing
for lasting
ingress protection



Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 08-for single door DBs, IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bar | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification label
- › With provision for DP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer + Outgoing			
IP 30 - Single Door				
4 way	2	2	DESPN004SDS	1625
6 way	2	4	DESPN006SDS	1705
8 way	2	6	DESPN008SDS	1965
12 way	2	10	DESPN012SDS	2330
16 way	2	14	DESPN016SDS	2855
18 way	2	16	DESPN018SDS	3320
IP 43 - Metal Door				
4 way	2	2	DESPN004DDS	2120
6 way	2	4	DESPN006DDS	2440
8 way	2	6	DESPN008DDS	2615
12 way	2	10	DESPN012DDS	3135
16 way	2	14	DESPN016DDS	3965
18 way	2	16	DESPN018DDS	4150
IP 43 - Glazed Door				
4 way	2	2	DESPN004GDS	2835
6 way	2	4	DESPN006GDS	3020
8 way	2	6	DESPN008GDS	3280
12 way	2	10	DESPN012GDS	3995
16 way	2	14	DESPN016GDS	4965
18 way	2	16	DESPN018GDS	5255
IP 54 - Metal Door				
4 way	2	2	DESPN00454S	7395
6 way	2	4	DESPN00654S	8245
8 way	2	6	DESPN00854S	8770
12 way	2	10	DESPN01254S	10070
16 way	2	14	DESPN01654S	11210
18 way	2	16	DESPN01854S	11460

Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 08-for single door DBs, IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB/Isolator/RCCB/RCBO as incomer and SPMCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
IP 30 - Single Door				
4 way	4	4+4+4	DETPPE004SDS	4235
6 way	4	6+6+6	DETPPE006SDS	5200
4 way	8	4+4+4	DETPN004SDS	4465
6 way	8	6+6+6	DETPN006SDS	5525
8 way	8	8+8+8	DETPN008SDS	6520
12 way	8	12+12+12	DETPN012SDS	9390
16 way	8	16+16+16	DETPN016SDS	11450
IP 43 - Metal Door				
4 way	4	4+4+4	DETPPE004DDS	4980
6 way	4	6+6+6	DETPPE006DDS	6190
4 way	8	4+4+4	DETPN004DDS	5210
6 way	8	6+6+6	DETPN006DDS	6490
8 way	8	8+8+8	DETPN008DDS	7790
12 way	8	12+12+12	DETPN012DDS	11620
16 way	8	16+16+16	DETPN016DDS	14420
IP 43 - Glazed Door				
4 way	4	4+4+4	DETPPE004GDS	6765
6 way	4	6+6+6	DETPPE006GDS	8130
4 way	8	4+4+4	DETPN004GDS	7040
6 way	8	6+6+6	DETPN006GDS	8570
8 way	8	8+8+8	DETPN008GDS	10160
12 way	8	12+12+12	DETPN012GDS	15585
16 way	8	16+16+16	DETPN016GDS	18730
IP 54 - Metal Door				
4 way	4	4+4+4	DETPPE00454S	16895
6 way	4	6+6+6	DETPPE00654S	19745
4 way	8	4+4+4	DETPN00454S	17860
6 way	8	6+6+6	DETPN00654S	21505
8 way	8	8+8+8	DETPN00854S	23510
12 way	8	12+12+12	DETPN01254S	33135
16 way	8	16+16+16	DETPN01654S	39770

For ordering old DBs, replace Cat no with "DB" instead of "DE".

Eg. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCB / Isolator / RCCB / RCBO as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing



Horizontal PPI DBs

IP 43 - Metal Door

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
IP 43 - Metal Door					
4 way	8	2+2+2	4+4+4	DEHPI004DD	9265
6 way	8	2+2+2	6+6+6	DEHPI006DD	10970
8 way	8	2+2+2	8+8+8	DEHPI008DD	13155
12 way	8	2+2+2	12+12+12	DEHPI012DD	18125
16 way	8	2+2+2	16+16+16	DEHPI016DD	21745



Tier PPI DBs

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
IP 43 - Metal Door					
6 way	8	2+2+2	6+6+6	DETP1006DD	11350
8 way	8	2+2+2	8+8+8	DETP1008DD	14230
10 way	8	2+2+2	10+10+10	DETP1010DD	14920
12 way	8	2+2+2	12+12+12	DETP1012DD	15805
16 way	8	2+2+2	16+16+16	DETP1016DD	18020
12 way	MCCB*	2+2+2	12+12+12	DETPL012DD	16905

*Suitable for 3 Pole & 4 Pole DU100H, DU100D, DN0-100D & DN0-100C MCCB as incomer

Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for
 - » Modular Incomer - FP MCB/Isolator/RCCB/RCBO as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing
 - » MCCB Incomer - MCCB* as incomer, DP RCCB/RCBO as sub-incomer and SP MCBs as outgoing



With Modular Incomer

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Sub-Incomer	Outgoing		
IP 43 - Metal Door					
4 way	8	4+4+4	4+4+4	DEPSG004DD	13605
6 way	8	4+4+4	6+6+6	DEPSG006DD	15340
8 way	8	4+4+4	8+8+8	DEPSG008DD	17115
12 way	8	4+4+4	12+12+12	DEPSG012DD	21230



With MCCB Incomer

Description	No. of Modules			Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Sub-Incomer	Outgoing		
IP 43 - Metal Door					
4 way	MCCB	4+4+4	4+4+4	DEPGL004DD	18715
6 way	MCCB	4+4+4	6+6+6	DEPGL006DD	21400
8 way	MCCB	4+4+4	8+8+8	DEPGL008DD	24750
12 way	MCCB	4+4+4	12+12+12	DEPGL012DD	27915

*Suitable for 3 Pole & 4 Pole DU100H, DU100D, DN0-100D & DN0-100C MCCB as incomer

Vertical TPN DB with MCCB Incomer [8537]



Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with insulated vertical phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for 3 pole and 4 Pole MCCB* as incomer and SP/TP MCCBs as outgoing



Up to 125A MCCB Incomer

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Outgoing		
IP 43 - Metal Door				
4 way	MCCB	4+4+4	DEVTL004DD	15180
6 way	MCCB	6+6+6	DEVTL006DD	17255
8 way	MCCB	8+8+8	DEVTL008DD	18995
12 way	MCCB	12+12+12	DEVTL012DD	25840
16 way	MCCB	16+16+16	DEVTL016DD	30825
IP 54 - Metal Door				
4 way	MCCB	4+4+4	DEVTL00454	31445
6 way	MCCB	6+6+6	DEVTL00654	35860
8 way	MCCB	8+8+8	DEVTL00854	38820

*Suitable for 3 Pole & 4 Pole DZO MCCB as incomer.
In case of any other MCCB frame requirement please contact nearest branch.

Vertical TPN DB with Modular Incomer [8537]



Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - Provided with insulated vertical phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- › With provision for FP MCCB/Isolator/RCCB/RCBO as incomer and SP/ TP MCCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
IP 43 - Metal Door				
4 way	8	4+4+4	DEVTM004DD	12835
6 way	8	6+6+6	DEVTM006DD	14300
8 way	8	8+8+8	DEVTM008DD	16600
12 way	8	12+12+12	DEVTM012DD	22390
16 way	8	16+16+16	DEVTM016DD	26715
IP 54 - Metal Door				
4 way	8	4+4+4	DEVTM00454	27135
6 way	8	6+6+6	DEVTM00654	29605
8 way	8	8+8+8	DEVTM00854	32690

Vertical TPN DB with MCCB Incomer [8537]



Up to 250A MCCB Incomer

Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer*	Outgoing		
IP 43 - Metal Door				
4 way	MCCB	4+4+4	DEVTH004DD	19725
6 way	MCCB	6+6+6	DEVTH006DD	22090
8 way	MCCB	8+8+8	DEVTH008DD	24295
12 way	MCCB	12+12+12	DEVTH012DD	29405
16 way	MCCB	16+16+16	DEVTH016DD	39515
IP 54 - Metal Door				
4 way	MCCB	4+4+4	DEVTH00454	36090
6 way	MCCB	6+6+6	DEVTH00654	39405
8 way	MCCB	8+8+8	DEVTH00854	40755

*Suitable for 3 pole and 4 pole DU250, DU250C & DN1 MCCB as incomer

Flexi/Row DB [8537]



Highlights

- › Conforms to IEC 61439-1 & 3
- › IK 09-for double door DBs
- › Available in CRCA sheet steel, RAL 9003, powder coated
- › Ready to use DBs - neutral bar/s with shroud/s | earth bar/s | sticking saddles | cement spill protector | cable ties | circuit identification labels
- › With provision to mount modular devices as per requirement



Description	No. of Modules Per Row	Cat. Nos.	M.R.P. (₹) Per Unit
IP 43 - Metal Door			
2 Row 28 Module	14	DEROW228DD	6630
3 Row 42 Module	14	DEROW342DD	7950
4 Row 56 Module	14	DEROW456DD	8645
4 Row 64 Module	16	DEROW464DD	10055

For ordering old DBs, replace Cat no with "DB" instead of "DE".

Eg. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

TPN Phase Selector DB [8537]



Highlights

- Conforms to IEC 61439-1 & 3
- IK 09-for double door DBs
- Available in CRCA sheet steel, RAL 9003, powder coated
- Ready to use DBs - Provided with 3 nos. of 63A E&A rotary switches | 3 nos. of rocker switches for phase identification | 100A insulated phase bus-bars | neutral bar/s with shroud/s | earth bar/s | sticking saddles | color-coded interconnecting wire set | cable ties | blanking plates and circuit identification labels
- With provision for - FP MCB/Isolator/RCCB/RCBO as incomer and SP MCBs as outgoing



Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
	Incomer	Outgoing		
IP 43 - Metal Door				
4 way	8	4+4+4	DEPSR004DD	16710
6 way	8	6+6+6	DEPSR006DD	16975
8 way	8	8+8+8	DEPSR008DD	18185
10 way	8	10+10+10	DEPSR010DD	19430
12 way	8	12+12+12	DEPSR012DD	20485

EV charging DB 8537]



Highlights

- Engineered specifically Charging application - 3.3 kW
- Robust earth leakage, short circuit and overload protection with RCBO-
- Factory fitted RCBO, switch and socket



Description	No. of Modules	Cat. Nos.	M.R.P. (₹) Per Unit
2 way EVDB	2	DEEVC002LD	*
4 way EVDB	4	DEEVC004LD	*

* For details, please contact nearest branch office

Enclosure [8537]



Highlights

- Conforms to IEC 61439-1 & 3
- Suitable for Surface and Flush mounting
- Available in CRCA sheet steel, RAL9003, powder coated
- With provision to mount MCB/Isolator/RCCB/RCBO and other modular devices



IP 30 - Metal Door

Description	No. of Modules	Cat. Nos.	M.R.P. (₹) Per Unit
IP 30 - Metal Door			
2 way	2	DEENC002SD	825
3 way	3	DEENC003SD	825
4 way	4	DEENC004SD	825
6 way	6	DEENC006SD	1280

For ordering old DBs, replace Cat no with "DB" instead of "DE".

Eq. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

Plug & Socket DB [8537]



Highlights

- Conforms to IEC 61439-1 & 3
- Suitable for Surface and Flush mounting
- Available in CRCA sheet steel, RAL9003, powder coated
- Loose Metal Plugs & Sockets conforms to IS 8804; available in Single Phase & Three Phase



Metal Plug & Socket

Plastic Plug & Socket

Description	No. of Pins	No. of Modules	Cat. Nos.	M.R.P. (₹) Per Unit
Metal Plug & Sockets				
10 A, 2 Pin + SC ^A	P + N	1	DEMPS110SD	2050
20 A, 2 Pin + SC ^A	P + N	1	DEMPS120SD	2205
20 A, 2 Pin + SC ^A	P + N	2	DEMPS220SD	2390
20 A, 3 Pin + SC ^A	3P	3	DEMPS320SD	4050
32 A, 3 Pin + SC ^A	3P	3	DEMPS332SD	4795
32 A, 3 Pin + SC ^A	3P	4	DEMPS432SD	5100
63 A, 5 Pin + SC ^A	3P+N+E	4	DEMPS463SD	17280
Plastic Plug & Sockets				
16 A, 3 Pin	P+N+E	2	DEPPS316SD	3355
32 A, 3 Pin	P+N+E	4	DEPPS332SD	3620
32 A, 5 Pin	3P+N+E	8	DEPPS532SD	6045
63 A, 5 Pin	3P+N+E	8	DEPPS563SD	15145

Metal Plug [8536]



Description	No. of Pins	Cat. Nos.	M.R.P. (₹) Per Unit
10 A, 2 Pin + SC ^A	P + N	MPS210P	255
20 A, 2 Pin + SC ^A	P + N	MPS220P	270
20 A, 3 Pin + SC ^A	3P	MPS320P	355
32 A, 3 Pin + SC ^A	3P	MPS332P	675

Note: Standard pack quantity - 20 nos.

Metal Socket [8536]



Description	No. of Pins	Cat. Nos.	M.R.P. (₹) Per Unit
10 A, 2 Pin + SC ^A	P + N	MPS210S	265
20 A, 2 Pin + SC ^A	P + N	MPS220S	290
20 A, 3 Pin + SC ^A	3P	MPS320S	400
32 A, 3 Pin + SC ^A	3P	MPS332S	675

^A SC-Scraping Earth

Note: Standard pack quantity - 20 nos.

DBs with provision for TV / Telephone splitters [8537]

New

Highlights

- › Distribution Boards equipped with provisions to mount TV / Telephone splitters
- › Available in SPN & TPN DBs
- › Communication DB equipped with provisions to mount 2 ONT, Spike guard, Data switch, TV / Telephone splitters



TV / Telephone



Communication DB

Cable End Boxes [8537]

Highlights

- › Available in CRCA sheet steel, RAL9003, powder coated
- › Can be either at the top or bottom of the distribution board

Description	Cat. Nos.	M.R.P. (₹) Per Unit
CEB for SPN DBs		
CEB-SPN Double Door, 4 way	DESPN004CBS	905
CEB-SPN Double Door, 6 way	DESPN006CBS	975
CEB-SPN Double Door, 8 way	DESPN008CBS	1090
CEB-SPN Double Door, 12 way	DESPN012CBS	1215
CEB-SPN Double Door, 16 way	DESPN016CBS	1710
CEB-SPN Double Door, 18 way	DESPN018CBS	1765
CEB for TPN DBs		
CEB-TPE Double Door, 4 way	DETPE004CBS	1170
CEB-TPE Double Door, 6 way	DETPE006CBS	1670
CEB-TPN Double Door, 4 way	DETPN004CBS	1225
CEB-TPN Double Door, 6 way	DETPN006CBS	1720
CEB-TPN Double Door, 8 way	DETPN008CBS	2165
CEB-TPN Double Door, 12 way	DETPN012CBS	3595
CEB-TPN Double Door, 16 way	DETPN016CBS	3630
CEB for Horizontal PPI DBs		
CEB-Horz. PPI Double Door, 4 way	DEHPI004CB	1815
CEB-Horz. PPI Double Door, 6 way	DEHPI006CB	2265
CEB-Horz. PPI Double Door, 8 way	DEHPI008CB	2840
CEB-Horz. PPI Double Door, 12 way	DEHPI012CB	3565
CEB-Horz. PPI Double Door, 16 way	DEHPI016CB	3875
CEB for VTPN DBs		
CEB-VTPN Double Door, Modular Incomer	DEVTMXXCB	1215
CEB-VTPN Double Door, MCCB Incomer	DEVTXXXCB	4285
CEB for Phase Segregated DBs		
CEB-PSG Double Door, 4 way	DEPSG004CB	3180
CEB-PSG Double Door, 6 way	DEPSG006CB	3790
CEB-PSG Double Door, 8 way	DEPSG008CB	4185
CEB-PSG Double Door, 12 way	DEPSG012CB	4660

DB Type	Description	No. of Modules		Cat. Nos.	M.R.P. (₹) Per Unit
		Incomer + Outgoing			
IP 43 - Metal Door					
SPN	6 way	2	4	DESPN006DDTV	4615
	8 way	2	6	DESPN008DDTV	4960
	12 way	2	10	DESPN012DDTV	6105
	16 way	2	14	DESPN016DDTV	7080
	18 way	2	16	DESPN018DDTV	8375
TPN	4 way	8	4+4+4	DETPN004DDTV	9070
	6 way	8	6+6+6	DETPN006DDTV	10475
	8 way	8	8+8+8	DETPN008DDTV	12490
Communication DB				DECOM01DD	*

* For details, please contact nearest branch office

DB Accessories

Busbar - Fork Type [8538]

Highlights

- › Available in Single Pole, Double Pole, Three Pole and Four Pole versions
- › Material : Copper



Description	Cat. Nos..	M.R.P. (₹) Per Unit	Std. Pack Qty.
SP 13 Mod	BSP13	405	5
SP 56 Mod	BSP56	1655	5
DP 12 Mod	BDP12	720	5
TP 12 Mod	BTP12	775	5
FP 12 Mod	BFP12	1535	5
End Caps for SP	ECP01	25	10
End Caps for DP/TP	ECP03	55	10
End Caps for FP	ECP04	90	10



Blanking Plates [8538]

Highlights

- › Available in One module and Half module

Description	Cat. Nos.	M.R.P. (₹) Per Unit	Std. Pack Qty.
One Module	BKP10	25	10
Half Module	BKP05	25	10



PDK02

Padlock [8301]

Highlights

- › Version with standard lock and a common key

Description	Cat. Nos.	M.R.P. (₹) Per Unit	Std. Pack Qty.
Lock and Key Kit	PDK02	705	5

For ordering old DBs, replace Cat no with "DB" instead of "DE".

Eg. - New DB Cat no for SPN 12W DD - DESPN012DDS, Old DB Cat no for same will be DBSPN012DDS. Old DBs are available till stock last.

General Terms

All prices are on Maximum retail price basis inclusive of all duties, GST & any other tax as applicable.

Warranty Policy

All products listed in the price list are covered by a warranty against manufacturing defects for a period of 18* months from the date of purchase. For Lauritz Knudsen MCBs & Isolators mounted inside Lauritz Knudsen Distribution Boards, an extended warranty of 5 years is provided.

In the event of a defect due to faulty workmanship or other associated reasons, we will, at our discretion, remedy the defect or replace the faulty parts or the entire product as soon as possible, free of cost.

However, the warranty is subject to proper usage, efficient maintenance, and does not cover defects arising from fire, accidents, inefficient maintenance, faulty operation, or deliberate or accidental damage. It also does not cover damage to power electronic components such as thyristors & IGBTs, which primarily fail due to overtemperature & over-voltage. Users need to take adequate precautions to eliminate these conditions. Manufacturer shall not be responsible & liable for any special, incidental, social or consequential (including lost profits) loss, consequential damages, injury or damages (punitive) of any kind solely attributable to defect or failure of its products. Manufacturer shall not be liable in any manner for the issue of or failure in the performance of other equipment the product is attached to.

Comprehensive Service Support

Lauritz Knudsen Electrical & Automation has over seven decades of experience in providing after sales service for low voltage distribution system in every type of industry & commercial complex in India

Lauritz Knudsen Electrical & Automation offers the following services, partnering you in your maintenance of low voltage distribution products:

- › Regular Maintenance
- › Preventive Maintenance Programme
- › On Call
- › Annual Maintenance Contract
- › Product Support for Managing Obsolescence-

Switchgear Training Centres



Pune

Lauritz Knudsen Electrical & Automation
Switchgear Training Centre
T-156 / 157, MIDC,
Bhosari, Pune - 411 026
Tel: 020-2712 0037 / 2712 0653
E-mail: STC-PUNE@LK-EA.com



Lucknow

Lauritz Knudsen Electrical & Automation
Switchgear Training Centre
C-6 & 7, UPSIDC,
P. O. Sarojininagar,
Lucknow - 226 008
Tel: 97944 54455
E-mail: STC-LUCKNOW@LK-EA.com



Delhi

Lauritz Knudsen Electrical & Automation
Switchgear Training Centre
A-25, Imperia Complex, First Floor
Mohan Cooperative Industrial Estate
Near Sarita Vihar / Mohan Estate Metro Station
Main Mathura Road, New Delhi - 110044
Tel: 9899020306 / 9720186726 / 9560845094
E-mail: STC-DELHI@LK-EA.com



Kolkata

Lauritz Knudsen Electrical & Automation
Switchgear Training Centre,
2nd Floor, Block BN3, Sector V,
Salt Lake City,
Kolkata - 700091, West Bengal
Tel: 7738717893 / 7797795567
E-mail: STC-KOLKATA@LK-EA.com



Vadodara

Lauritz Knudsen Electrical & Automation
Switchgear Training Centre
Behind L&T Knowledge City,
Near Village Ankhol,
Vadodara - 390019
Tel: 0265 6147805 / 6147808
E-mail: STC-VADODARA@LK-EA.com



Coonor

Lauritz Knudsen Electrical & Automation
Switchgear Training Centre
Ooty-Coonoor Main Road
Yellanahalli P.O.,
The Nilgiris - 643 243
Tel: 0423 251 7107
E-mail: STC-COONOOR@LK-EA.com

Electrical Standard Products (ESP) Offices

HEAD OFFICE

Lauritz Knudsen Electrical & Automation, A/600, Shil-Mahape Road, TTC Industrial Area, MIDC Thane, Navi Mumbai, 400 710, Maharashtra.

Tel: 022-6722 6300 | Fax: 022-6705 1112 | e-mail: CIC@LK-EA.com

BRANCH OFFICES

Lauritz Knudsen Electrical & Automation
C-201, The First Commercial Complex,
B/S Keshavbaug Party Plot, Vastrapur,
Ahmedabad - 380 015
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Shri Daneshwari, 1st Floor,
Plot No. 17, 2nd Cross, Near Old Income
Tax Office Road, Vidyanagar,
Hubballi - 580 021
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
No.10, Fortuna Towers, 2nd Floor,
Rana Pratap Marg, Near NBRI,
Lucknow - 226 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
A06/A07, Second Floor,
Grand Chandra Complex, Frazer Road
Patna - 800 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Wework Central, #36 Infantry Road,
Bengaluru - 560 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
AWFIS Space Solutions, Prestige Phoenix,
4th floor, 1405, Umanagar, Begumpet,
Hyderabad - 500 016
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
El Dorado Building, 3rd Floor, 6,
Venkatraman Street, Chinna Chokkikulam,
Madurai - 625 002
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
UrbanWrk, 5th Floor, Sai Radhe,
Raja Bahadur Mill Road, Behind Hotel
Grand Sheraton, Sangamwadi
Pune - 411 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Work loop Unit-612, 6th Floor,
Esplanade One, Rasulgarh,
Bhubaneswar - 751 010
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Workie, 214 - 2nd Floor,
Apollo Premier, PU-4,
Scheme No. 54, Vijay Nagar Square,
Indore - 452 010
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Bestech Business Park,
Tower - A, 2nd floor, Sector - 66
Mohali - 160059
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Office No. 211 & 212, Pithalia Plaza,
KK Road, Near Fafadih Chowk,
Raipur - 492 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
801 Word Level-8, No. 28,
SIDCO Industrial Estate, Guindy,
Chennai - 600 032
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Office No. 430, 4th Floor,
Jaipur Electronic Market, Riddhi Siddhi,
Gopalpura Bypass,
Jaipur - 302 018
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
TC II, Tower B, PRIMA BAY Gate No. 5,
Saki Vihar Road Powai,
Mumbai - 400 072
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
DevX 4th Floor, A Wing, Om 9 Square,
150 Ft Ring Road, Near Nana Maya Circle,
Opp Silver Heights,
Rajkot - 360 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Playworkz Coworking Space
43 & 44, 3rd Cross,
Bharathy Colony, Peelamedu,
Coimbatore - 641 004
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
GDR Siddha, Ground Floor, N Road
Bistupur, Opposite St. Mary's Church,
Jamshedpur - 831 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Unnati Building, 2nd Floor,
Automation Campus, A-600, TTC Industrial
Area Shil-Mahape Road, Mahape,
Navi Mumbai - 400 710
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
10th Floor, Titaanium Business,
Bhimrad Road, Althan
Surat - 395 017
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
3rd Floor, 1&2 Vijay Park,
Main Chakrata Road, Opp. Anandam,
Near Ballupur chowk,
Dehradun - 248 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Business Communication Centre
2nd Floor, Chiramel Chambers,
Kurusipally Road, Ravipuram,
Kochi - 682 015
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
M1 & M2, Mezzanine Floor,
Himalaya Excellency,
Plot No. C-47, Pratap Nagar Square,
Nagpur - 440 022
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
11th Floor, Block-D, Notus IT Park,
Sarabhai Campus, Bhailal Amin Marg,
Vadodara - 390 023
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Ground Floor, B-27,
Biplab Rashbihari Sarani,
Sector 2A, Bidhan Nagar,
Durgapur - 713 212
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz & Knudsen Electrical & Automation
207, 2nd floor, Revolution Complex,
Station Road, E Ward,
Next to Pedestrian Bridge,
Kolhapur - 416 001
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
2nd Floor, Samarth House,
Opposite Titan World,
Samarth Nagar, Mahatma Nagar,
Nasik - 422 005
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
Qubexpro Business Centre,
4th Floor, V Mall, Above Lifestyles,
Facor Layout, Waltair Uplands,
Visakhapatnam - 530 003
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
6th Floor, Exotica Greens, A Block, 191,
R G Baruah Road, Guwahati Central,
Guwahati - 781 005
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
2nd Floor, BN3, Salt Lake, Sector-V,
Kolkata - 700 091
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Lauritz Knudsen Electrical & Automation
A-25, 1st Floor, Imperia Complex,
Mohan Corporate Industrial Estate,
Near Sarita Vihar Metro Station,
Mathura Road,
New Delhi - 110 044
Phone No: 022-6932 7800
e-mail: CIC@LK-EA.com

Product improvement is a continuous process. For the latest information and special application, please contact any of our offices listed here. Product photographs shown for representative purpose only.



Lauritz Knudsen Electrical & Automation, Electrical Standard Product

A/600, Shil-Mahape Road, TTC Industrial Area, MIDC Thane, Navi Mumbai, 400 710, Maharashtra, Phone No: 022-6722 6300 | Web: www.LK-EA.com

Customer Interaction Center (CIC)

Phone no: 022-6932 7800

Web: www.LK-EA.com | e-mail: CIC@LK-EA.com